

AFIS422VSX-B Advanced Fast Idle System

2009-2019 Ford E-Series, all engines
2009-2010 Ford F-250 - F-550, all engines
2014-2020 Ford F53/F59, 6.8L engine
2014-2016 Ford Transit Connect
2009-2023 Chevrolet Express / GMC Savana
2015-2023 Chevrolet Silverado / Sierra
2011-2014 American General MV-1 4.6L
2016-2023 Isuzu NPR, gas only
2019 Chevy LCF (Low Cab Forward Trucks)
2019 International CV



Overview

The Advanced Fast Idle System (AFIS) elevates engine idle speed in response to a number of triggers in order to assist electrical or mechanical systems on the vehicle.

Options

AFIS422VSX-B — Single OBDII connector Data Link Harness

AFIS422VSX-BP — Two connector "T" Data Link harness

AFIS422VSX-BIP — Two connector white panel mount "T" Data Link harness

Installation Instructions

Disconnect vehicle battery before proceeding with installation.



WARNING
Disconnect the battery to
prevent setting a check engine
light.

IMPORTANT—READ BEFORE INSTALLATION

It is the installer's responsibility to route and secure all wiring harnesses where they cannot be damaged by sharp objects, mechanical moving parts and high heat sources. Failure to do so could result in damage to the system or vehicle and create possible safety concerns for the operator and passengers. Avoid placing the module where it could encounter strong magnetic fields from high current cabling connected to motors, solenoids, etc. Avoid radio frequency energy from antennas or inverters next to the module. Avoid high voltage spikes in vehicle wiring by always using diode clamped relays when installing upfitter circuits.

AFIS422 Module

Remove the lower dash panel below the steering column area and find a suitable location to mount the AFIS422 module. Locate the module in an area away from external heat sources (engine heat, heater ducts, etc.). Do not mount the module until all wire harnesses are routed and secure. The last step of the installation is to mount the module.

Data Link Harness (4-Pin Connector)

1. Locate the vehicle's OBDII Data Link Connector, mounted below the lower left dash panel. Plug the Red connector from the AFIS Data Link Harness into the vehicle OBDII connector. Ensure the connection is fully seated and secured with the supplied wire tie.
2. Secure the AFIS Data Link harness so that it does not hang below the lower dash and plug the (4-pin connector) from the Data Link Harness into the 4-Pin connector on the AFIS module.




AFIS422VSX-BP/BIP "T" Data Link Harness

1. Locate the vehicle OBDII Data Link Connector, mounted below the lower left dash panel.
2. Remove the mounting screws for the OBDII connector. Plug the Red connector from the AFIS422VSX-BP Data Link Harness into the vehicle's OBDII connector. Ensure the connection is fully seated and secure with the supplied wire tie.
3. Mount the Black pass through connector from the AFIS422VSX-BP Data Link Harness in the former location of the vehicle's OBDII connector.
4. Secure the AFIS422VSXP-B Data Link harness so that it does not hang below the lower dash and plug the 4-pin connector from the Data Link Harness into the 4-Pin connector on the AFIS422VSX-B module.



AFIS Harness (8-Pin Connector) Fast Idle Engage Input, Green wire

1. Attach the AFIS Harness connector Pin #8 Green wire to any equipment that provides a ground signal when the fast idle needs to be engaged. (PTO, pump, etc.). **Note:** The Green wire can also be connected to equipment providing a 12V signal, if programmed. See below for programming instructions.
2. Plug the 8-pin connector from the AFIS Harness into the 8-Pin connector on the module.



VBAT Low Fast Idle Trigger Disable— Black wire loop

The system is configured from the factory for Fast Idle to be triggered when the battery voltage (VBAT) drops below 12.5V. If the VBAT Low Fast Idle Trigger is not desired, it may be disabled by cutting the Black wire (loop) on the 8-Pin connector between Pin #1 & Pin #3.



Configurable Idle Speed - Gray wire

The AFIS422VSX-B allows the user to change the fast idle RPM during installation. The default speed is 1500 RPM gas / 1200 Diesel, but the user can select any speed between 900 RPM and 2000 RPM in 50 RPM increments. To change idle speed:

1. Locate the Gray wire in the harness which connects to the 8 pin Molex connector.
2. Pull this wire out of the loom to expose the bare copper end.
3. Place the vehicle in Fast Idle by grounding the Manual Trigger Green wire. With the engine in Fast Idle, momentarily grounding the Gray wire (RPM Configuration input) increases the idle speed by 50 RPM. When the idle speed reaches the maximum allowable speed for the particular engine, it will roll back around to 900 RPM. Wherever the user stops, this RPM becomes the new default Fast Idle speed, even through key cycles.
4. After the vehicle is set to the desired fast idle speed, insert the end of the Gray wire into the harness tubing and use tape to secure.



Note: Some vehicle PCM's will limit Fast Idle to less than 2000 RPM. Continue momentarily grounding the Gray wire and the RPM will eventually roll back around to 900 RPM. Do not leave the RPM's set in a range that the engine RPM is not responding to, as this may cause Fast Idle issues.

Park Brake Fast Idle Trigger Enable/Disable

The AFIS422VSX-B is configured from the factory for Fast Idle **not** to be triggered when the Park Brake is applied. If the Park Brake Fast Idle trigger is desired, it may be enabled (or disabled) by the following procedure:

With key on, place the transmission in neutral, apply the Park Brake and press the Service Brake three times within 5 seconds. Upon successful reprogramming, the on-board LEDs will briefly flash as a confirmation. The user must cycle the key for the change to take affect.

A/C Fast Idle Trigger

The system is configured from the factory for Fast Idle to be triggered when the A/C clutch is engaged and will stay engaged until the next key cycle, or a precondition is violated.

Fast Idle Pin-8 Trigger, Active: Ground or 12V signal Enable/Disable

The module is configured from the factory for an active ground fast idle trigger. To change this to an active 12V trigger:

Turn the key on, place the transmission in neutral, apply the Service Brake, pull out on the Park Brake, release and apply the Park Brake four times within 5 seconds. Upon successful reprogramming, the LEDs will flash as a confirmation. The user must cycle the key for the change to take affect. Repeat to reverse back to a ground trigger.

Post Installation System Operation Test

Perform the following tests before mounting the module, to allow easy viewing of the diagnostic LED's, if needed.

1. Place transmission in Park and start the engine. Vehicle may enter Fast Idle if VBAT is low. Either wait to see if the battery charges and Fast Idle stops, or place a charger on the vehicle to disable the VBAT low trigger to allow testing of other triggers.
2. Manually engage Fast Idle by having aftermarket vehicle equipment ground the Green wire. Engine speed will increase to the set RPM level. If this does not occur, check harness connections. Also see diagnostics below.
3. Assuming Fast Idle engaged, keep the Green wire grounded, and depress the Service Brake for 1 second. Fast idle will temporarily disengage anytime the Service Brake is depressed, but will automatically reengage after approximately 2 seconds once the Brake pedal is released.
4. Place transmission shift lever in the "Neutral" position. (Green wire still grounded). The system must not activate Fast Idle.


The AFIS422VSX-B is properly installed only if it passes all of the above steps.

Module Mounting

Ensure all harnesses are properly connected and routed and are not hanging below the dash area. Mount the AFIS422VSX-B module using screws or double sided tape and reinstall all panels.

Diagnostics

Diagnostic mode is entered by momentarily shorting the two gold "Test" pads together on the module. The module provides diagnostic LEDs which illuminate according to the following table. To exit this mode, cycle the key or momentarily ground the "Test" pad again.



Fast Idle Status Codes

Status Codes provide the current status of the Fast Idle system. The on-board "Status" LED will flash a 2-digit code as shown in the table. The first digit will flash, wait half a second, flash the second digit, then wait one second before the next code. The Status Codes continue to flash until the module is reset (cycle key), or the test input is momentarily grounded again.

LED #	Diagnostic Mode LED Descriptions
1	On when fast idle is engaged
2	On when Green trigger wire is active
3	On when Gray RPM set wire is grounded
4	On when the Parking Brake is applied with the parking brake trigger enabled
STATUS	Continuously flashes two digit status codes. See Status Code table

AFIS Status Codes	
Status Code	Description
1-1	Ready for fast idle
2-3	Triggered: Parking Brake
2-4	Triggered: VBAT Low
2-5	Triggered: A/C Boost
2-8	Triggered: Manual Input
3-1	RPM > 2800
3-2	RPM < 200
3-3	TR not = to PARK
3-4	VSS not = to 0 MPH
3-5	Service Brake applied
3-7	Unsafe; Need to cycle TR
3-8	ECT > 230°F

Leave in Vehicle
Operating Instructions AFIS422VSX-B Advanced Fast Idle System
Transit Application

2009-2019 Ford E-Series, all engines
2009-2010 Ford F-250 - F-550, all engines
2014-2020 Ford F53/F59, 6.8L engine
2014-2016 Ford Transit Connect
2009-2023 Chevrolet Express / GMC Savana
2015-2023 Chevrolet Silverado / Sierra
2011-2014 American General MV-1 4.6L
2016-2022 Isuzu NPR, gas only
2019 Chevy LCF (Low Cab Forward Trucks)
2019 International CV

System Operation

The Advanced Fast Idle System (AFIS) elevates engine idle speed in response to a number of triggers in order to assist electrical or mechanical systems on the vehicle.

Fast Idle may be initiated by either a manual trigger (Green wire being grounded), a low battery voltage (low VBAT) condition, the A/C clutch engaging, or if enabled, by setting the Park Brake.

Fast Idle will only occur when the required preconditions are met, as listed below. Fast Idle operation will be terminated by a loss of **any** of the preconditions, or removal of the trigger(s).

Fast Idle Triggers		
Trigger Name	Trigger Conditions	Disable Conditions
Manual Engage	Fast Idle Engage Green wire grounded Or 12V input enabled (based on setting)	Fast Idle Engage Green wire not grounded Or not 12V (based on setting)
VBAT Low	VBAT < 12.5V	Precondition Violation
Parking Brake	Parking Brake applied	Parking Brake Released
A/C Boost	A/C Clutch (engaged)	Precondition Violation

Fast Idle Preconditions

The following preconditions must be met prior to initiating Fast Idle operation.

- Vehicle speed zero
- Transmission in Park
- Accelerator pedal must not be applied
- Engine Coolant temperature must be less than 230°F
- Engine RPM must be greater than 200 and less than 2800.
- Service Brake not applied

The following are options that are configurable at the factory for OEM customers. The default values are shown.

AFIS422VSX-B


Idle RPM: 1500 gas / 1200 Diesel

VBAT Low: 12.5V

A/C Trigger: Enabled

Parking Brake Trigger: Disabled


AFIS422VSX-B Data Link Harness Harness Part # S-H35AX



- 1 — RED — (Battery Voltage)
- 2 — YELLOW — (CAN High Speed/High)
- 3 — GRAY — (Ground)
- 4 — BROWN — (CAN High Speed/Low)

Back of Connector

Data Link Harness-
Attach To OEM OBDII
Connector




- 1 — RED — (Battery Voltage)
- 2 — YELLOW — (CAN High Speed/High)
- 3 — GRAY — (Ground)
- 4 — BROWN — (CAN High Speed/Low)

Back of Connector


AFIS422VSP-B Data Link Harness Harness Part # S-H07DX or S-H07FX (Isuzu Only)



Pass Through OBDII
Connector



AFIS 422 VSX-B
Part # S-M1100-33



Back of Connector

- 1 — BLACK —
- 2 — N/C —
- 3 — BLACK —
- 4 — GRAY —
- 5 — N/C —
- 6 — N/C —
- 7 — N/C —
- 8 — GREEN —

VBAT Low Trigger

RPM Configuration (ground input)

Fast Idle Engage Input 1 (active ground input)(default)

Submit product registration at www.intermotive.net

If the AFIS422VSX-B fails any step in the Post Installation Test, review the installation instructions and check all connections.
If necessary, call Intermotive Technical support at (530) 823-1048