

**B-IDLE517**  
**Idle Lock™ Anti-Theft**  
**2020 - 2024 Ford Transit\***  
Contact InterMotive for additional vehicle applications.



**\* For vehicles with the OEM Gateway connector located below the lower left dash panel (with a Black OBDII connector). For vehicles with the Gateway located behind the glovebox (White OBDII connector), use the G-IDLE517.**

## Introduction

Idle-Lock is an anti-theft system that allows the engine to idle with the key removed from the ignition and the shifter locked in park. The system is activated by pressing a momentary enable switch and removing the key within three seconds. The system also provides a shift lock input that can be used as an interlock for the rear door.

## Installation Instructions

**Disconnect vehicle battery before proceeding with installation**



**WARNING**  
Disconnect the battery to prevent setting a check engine light.

## CAUTION

All electronic products are susceptible to damage from Electrostatic Discharge or ESD. Ground yourself before handling or working with the module and harnessing by first touching chassis ground, such as the barrel of the cigarette lighter.



It is the installer's responsibility to route and secure all wiring harnesses where they cannot be damaged by sharp objects, mechanical moving parts and high heat sources. Failure to do so could result in damage to the system or vehicle and create possible safety concerns for the operator and passengers. It is important to avoid placing the module where it could encounter strong magnetic fields from high current cabling connected to motors, solenoids, etc. Also avoid radio frequency energy from antennas or inverters next to the module. Finally, avoid high voltage spikes in vehicle wiring by always using diode clamped relays when installing upfitter circuits.

## B-IDLE517 Module


Remove the lower dash panel below the steering column and find a suitable location to mount the module. Locate the module in an area away from excessive heat sources (engine, heater ducts, etc.). Ensure when routing harnesses that the tilt steering column does not contact them in the full down position. When installing the harnesses, leave several inches of take-out such that the module can be removed if necessary.

Do not mount the module until all wire harnesses are routed and secure. The last step of the installation is to mount the module.

## Installation Instructions (continued)

### 24-pin Data Link Harness (6-pin connector)


1. Locate the vehicles Gateway Module. It will be mounted below the lower left dash panel.
2. Remove the harness behind the Gateway module by pressing the locking tab and pulling outward.
3. Plug the Female side of the Intermotive Gateway Harness into the back of the Gateway module. Ensure the connection is fully seated and secured by the locking tab.
4. Plug the Male side of the Intermotive Data Link Harness into the Gateway harness.
5. Secure the Gateway harness so that it does not hang below the lower dash panel.



### Ford Transit Ignition Switch

1. Remove the lower dash trim panel.
2. Remove the lower steering column trim cover.
3. Locate the ignition switch connector (C250) and disconnect it from the ignition switch.
4. Install the Idle-Lock harness between the Ignition Switch and the OEM connector.

Transit  
C250  
Front of  
Connector



## Ford Transit Shift Lock

- Remove the cup holder.



- Locate connector 2810 (12-pin connector). Remove the OEM connector and plug it into the mating 12-pin connector T-harness supplied with the B-IDLE517. Plug the remaining male connector into the OEM cavity.



**I/O Wiring, Features, and Descriptions:** (Solder and heat shrink all connections)

### **Shift Lock Request Input (Active Low)**

Pin 3, Green-White wire of the 4 pin connector is the Shift Lock Request Input. This input could be connected to the rear door switch to lock the shifter in park if the door is open.

### **Shift Lock Request Override Input (Active Low)**

Pin 5, Pink wire of the 12 pin connector is the Shift Lock Request Override Input. This input should be connected to a momentary switch that will override shift lock due to the Shift Lock Request Input. This input will allow the operator to temporarily override shift lock to shift the transmission out of park in the event of a bad door switch. It will only allow override if the key is in the ignition and the switch turned to the run position. **InterMotive strongly recommends installing this switch.**

### **Lock Output (Active High)**

Pin 2, White wire of the 12 pin connector is the Idle-Lock output. This output (500mA max current) can control installer supplied normally closed relays to lock/disable equipment when Idle-Lock is active. This minimizes possible theft when Idle-Lock is active and the vehicle is unattended.

When Idle-Lock is enabled, this output becomes active after 10 seconds. This output remains active until the key is back in the run position.

### **Idle-Lock Active Output (Active High)**

Pin 11, Yellow wire of the 12 pin connector is the Idle-Lock Active output. This output (500mA max current) can control installer supplied normally closed relays or auxiliary indicator LEDs. When Idle-Lock is enabled, this output becomes active. This output remains active until the key is back in the run position. Mounted in an appropriate location these indicators will allow the operator to easily determine if Idle-Lock mode is active.

### **Alarm Output (Active Low)**

Pin 8 (Orange wire) on the 12-pin connector will output a Ground signal (500mA max current) for 20 seconds anytime Idle-Lock is enabled and the Service Brake is pressed or someone attempts to shift out of Park. This can be attached to an alarm or lights to alert individuals outside the vehicle that the vehicle is being tampered with.

**Note: The Alarm Output is rated at 1/2A and is intended to drive relay coils or other low current loads. When driving relays, a diode-protected type must be used. InterMotive recommends Digi-Key #PB682-ND Relay.**

### **Idle-Lock Enable Switch and Active LED**

An LED is provided in the kit which illuminates when Idle-Lock is active.

1. Drill a 16mm (0.630") hole in the desired mounting location. One possibility is the dash panel to the left of the Steering Wheel.
2. Route the LED harness through the hole and mount the LED in the hole.
3. Slide the LED's lock nut onto the harness and snug it down onto the back of the LED.
4. Plug in the 4 pin (Black) connector of the LED harness into the mating connector on the Idle-Lock main harness.
5. Apply optional "Idle-Lock Enable/Active" label included in the kit.



### **B-IDLE517 Module Mounting**

Ensure all harnesses are properly connected and routed, and are not hanging below the dash area. Mount the module as described on page one and secure with supplied screws or double sided tape.

### **B-IDLE517 Harness (4 Pin connector and 12 Pin connector)**

1. Plug the B-IDLE517 4 Pin connector into the mating 4 pin connector on the B-IDLE517 module.
2. Plug the B-IDLE517 12 Pin connector into the mating 12 pin connector on the B-IDLE517 module.

### **Reconnect the vehicle battery**

## Post Installation Operational Test

**Test 1.** Start the Engine.

**Test 2.** While the engine is running, enable Idle-Lock by asserting the enable request input.

- The Red LED will flash five times and then blink every two seconds.
- Remove the key from the ignition within 3 seconds, the engine will continue to idle.
- Idle-Lock is now active.

**Test 3.** Attempt to shift the vehicle out of Park. The system will keep the shifter locked. If the Alarm Output (Pin 8 on the 12-pin connector) has been connected to an alarm or lights, they may activate for 20 seconds.

**Test 4.** Verify that the Lock Output disables/locks equipment at the proper times (if wired).

**Test 5.** Insert key and turn to RUN. The vehicle should be able to shift out of Park.

- The system will deactivate (shut down engine) if anyone defeats the OEM shift lock mechanism and shifts the vehicle out of Park.


**If the system fails any of the above tests, check the related wiring. If necessary, call InterMotive Technical Support at 530-823-1048. Do NOT release vehicle for service unless it has passed ALL of the above tests.**

**B-IDLE517**  
**Idle Lock™ Anti-Theft**  
**2020 - 2024 Ford Transit**  
**Contact InterMotive for additional vehicle applications.**



Idle-Lock is an anti-theft system that allows the engine to idle with the key removed from the ignition and the shifter locked in park. The system is activated by pressing a momentary enable switch and removing the key within three seconds. The system also provides a shift lock request input that can be used as an interlock for the rear door.

- Idle-Lock is enabled by removing the key from the ignition within 3 seconds of asserting the Idle-Lock enable input. Transmission must be in Park and engine must be running.
- To prevent unattended vehicle theft (Idle-Lock active), the shifter will remain locked, and the Lock Output will remain active.
- Inserting the key and turning it to Run restores normal operation. The Lock Output will turn off.
- The system may have an input to lock the shifter if the rear door is open. A momentary override switch will be installed to bypass shift lock due to the rear door in the case of a faulty door switch.
- Depending on how the vehicle has been upfit, the horn may honk and/or lights may flash if the Service Brake is pressed or somebody attempts to shift out of Park while Idle-Lock is enabled.



**Submit product registration at [www.intermotive.net](http://www.intermotive.net)**

If the Idle-Lock 517 fails any step in the Post Installation Test, review the installation instructions and check all connections. If necessary, call InterMotive Technical Support at (530) 823-1048.