## CATalert<sup>™</sup> Order Spec Sheet (Product Configuration Form)

## INTERMOTIVE VEHICLE CONTROLS Proudly distributed by

## Proudly distributed by LGS GROUP AUTOMOTIVE TECHNOLOGIES

## **Directions:**

- 1. Complete form to specify custom configurations for your CATalert.
- 2. Submit this form with your order to sales@lgs-group.com.

PURCHASEF	RINFORMATION	INTERNAL ONLY
Date		Config. Name
Company Nar	me	- Date Created
Contact Name	e	Part Number
Phone Number	er	
Email Address	S	-
Vehicle Make Vehicle Model		install vehicle's make, model and year. This information is needed for accurate
Vehicle Year   Vehicle Engine		
NOTES		_ configuration.
CATALTYIC (	CONVERTER QUANTITY	
Number of catalytic converters on the vehicle:		
	□ 1 □ 2 (Default) □ 3	
HORN ALARI	M	
CATalert will activate the horn if an attempt is made to remove the catalytic converter or disable the alarm.		
1 min - 60 mins (Default 5 mins)		
ADDITIONAL	. OUTPUT	
Yellow wire, PIN 7. Can be used for telematic devices, lights, etc.		
☐ Power <i>(Default)</i> ☐ Ground		
FEATURE FOR PURCHASE		
☐ Auxiliary Horn (-H Option)		
Faster and less complicated installation process than wiring to the OEM horn.		