Gateway Order Spec Sheet (Product Configuration Form)

Directions:

- 1. Complete form to specify custom configurations for your GTWY508.
- 2. Submit this form with your order to orders@lgs-group.com.

☐ Fast Idle Auto Triggers Disabled* (NAT)

*Heater Boost AC Activation





PURCHASER INFORMATION			INTERNAL ONLY						
Date				Config. Name					
Company Name			_						
Contact Name				Date Created					
Phone Number				Part Number					
Email Address				Ordoro will	not bo	araaaaa	ad with	out the	
Vehicle Make Vehicle Model				Orders will not be processed without the					
Vehicle Year Vehicle Engine				This information is needed for accurate					
	configuration.								
I/O PORT CONFIGURATIONS									
 Choose four (4) options below (one for each Pin). For a single function, select "X" For a multiple "AND" function, select "Y" For a multiple "OR" function, select "Z" 2. Choose the parameter and enter the value for the pin to provide a ground signal (if applicable).									
OPTIONS PID	PARAMET	rer		VALUE		PIN 3 1/02	PIN 4 1/0 3	PIN 10 1/O 4	
A/C Clutch Engage (AC)	☐ On	☐ Off	N/A						
Battery Voltage (VPWR)	☐ Above	☐ Below		Volts					
Engine Coolant Temp (ECT)	☐ Above	Below		°F					
Engine Speed (RPM)	☐ Above	☐ Below		RPM					
Grounded Input: Fast Idle (INPUT1)	N/A		N/A	4	_	_	_		
Grounded Input: Shift Lock (INPUT1)	N/A		N/A	Ą	_	-	_		
Intake Air Temp (IAT)	☐ Above	☐ Below		°F					
Park Brake (PB)	☐ On	☐ Off	N/A	4					
SEIC Output (2020 Ford 6.7L only)	N/A		N/A	4					
Service Brake Applied (SB)	☐ On	☐ Off	N/A	4					
Transmission Cntrl Ind Lamp (TCIL)	☐ On	☐ Off	N/A	4					
Transmission Fluid Temp (TFT)	☐ Above	☐ Below		°F					
Transmission Range (TR)	□P □R □N □D		N/A	4					
Vehicle Speed (VSS)	☐ Above	Above 🗌 Below		MPH					
Vehicle Speed (VSS)	Square Wave		2.2	Hz/MPH		 	—	_	
ADDITIONAL FEATURES									
☐ BrakeMax Controller Enabled ☐ Battery Voltage for Fast Idle Enabled									

Volts

0V - 20V