Gateway 508 Order Spec Sheet (Product Configuration Form)

Directions:

- 1. Complete form to specify custom configurations for your GTWY508.
- 2. Submit this form with your order to sales@lgs-group.com.

☐ Fast Idle Auto Triggers Disabled* (NAT)

*Heater Boost AC Activation





PURCHASER INFORMATION			INTERNAL ONLY				
Date							
Company Name			Config. Na	ame			
Contact Name			Date Creat	ted			
Phone Number			Part Number				
	_						
Vehicle Make Vehicle Model			Orders will not be processed without the				
			This is for any time in a second of for a second of				
Vehicle Year Vehicle Engine			configuration.				
I/O PORT CONFIGURATIONS							
 Choose four (4) options below (one for each Pin). Choose the parameter and enter the value for the pin 							
 For a single function, select "X" to provide a ground signal (if applicable). For a multiple "AND" function, select "Y" 							
 For a multiple "AND" function, select "Y" For a multiple "OR" function, select "Z" 							
OPTIONS PID	PARAMETER		VALUE	PIN 9	PIN 3	PIN 4	PIN 10
OFTIONS FID	FANAIVILI	LN	VALUE	1/01	1/02	1/03	1/04
A/C Clutch Engage (AC)	☐ On	☐ Off	N/A				
Battery Voltage (VPWR)	☐ Above	☐ Below	Volts				
Engine Coolant Temp (ECT)	☐ Above	Below	°F				
Engine Speed (RPM)	☐ Above	Below	RPM				
Grounded Input: Fast Idle (INPUT1)	N/A		N/A	_	_	_	
Grounded Input: Shift Lock (INPUT1)	N/A		N/A	_	–	—	
Intake Air Temp (IAT)	☐ Above	☐ Below	°F				
Park Brake (PB)	☐ On	☐ Off	N/A				
SEIC Output (2020 Ford 6.7L only)	N/A		N/A				
Service Brake Applied (SB)	☐ On	☐ Off	N/A				
Transmission Cntrl Ind Lamp (TCIL)	☐ On	☐ Off	N/A				
Transmission Fluid Temp (TFT)	☐ Above	☐ Below	°F				
Transmission Range (TR)			N/A				
Vehicle Speed (VSS)	☐ Above ☐ Below		MPH				
Vehicle Speed (VSS)	Square Wave		2.2 Hz/MPH		_	_	_
ADDITIONAL FEATURES							
ADDITIONAL FEATURES							
☐ BrakeMax Controller Enabled ☐ Battery Voltage for Fast Idle Enabled							
BelowVolts							

0V - 20V