IdleLock 751 Order Spec Sheet (Product Configuration Form)

INTERMOTIVE VEHICLE CONTROLS

Directions:

- 1. Complete form to specify custom configurations for your IDLE751.
- 2. Submit this form with your order to orders@lgs-group.com.



PURCHASER IN	FORMATION		
Date			
Company Name			NTERNAL ONLY
Contact Name _		С	config. Name
Phone Number		D	ate Created
			art Number
NOTES			art Number
VEHICLE DETAILS			
Orders will not be processed without the install vehicle's make, model and year.			
Vehicle Make	Vehi	cle Model	
Vehicle Year	Vehi	cle Engine	
Shifter Type: ☐ Column (lever) Shifter ☐ Rotary (dial) Shifter			
KEY FOB			
Deactivation Range:			
	☐ Standard Key fob must be in the driver's seat to shift the vehicle out of Park.		
	☐ Extended Key fob needs to be within 5 feet of the vehicle to shift out of Park.		
HORN ALARM			
IdleLock will activate the horn if an attempt is made to shift the vehicle out of Park without the key.			
	☐ Enabled (Default) ☐ Disabled		
Ц	Litabled (Delault) Disabled	4	
ADDITIONAL FE	ATURES FOR PURCHASE		
	Auto Lock (-E Option)	☐ Engi	ine Off (-K Option)
	IdleLock will automatically lock the vehicle doors after the system has been enabled.	Brak	ts off the engine if the Service ke is pressed without the fob ag detected.