IdleLock 751 Order Spec Sheet (Product Configuration Form)

INTERMOTIVE VEHICLE CONTROLS

Directions:

- 1. Complete form to specify custom configurations for your IDLE751.
- 2. Submit this form with your order to sales@lgs-group.com.



PURCHASER IN	FORMATION			
Date				
Company Name		INTERNAL ON	INTERNAL ONLY	
Contact Name		Config. Name		
Phone Number		Date Created		
Email Address		Dort Number		
NOTES		Fait Number		
VEHICLE DETAIL	.S			
Orders will not be processed without the install vehicle's make, model and year.				
Vehicle Make	Vehi	cle Model		
Vehicle Year	Vehi	cle Engine		
Shifter Type: ☐ Column (lever) Shifter ☐ Rotary (dial) Shifter				
KEY FOB				
Deactivation Range:				
	☐ Standard Key fob must be in the driver's seat to shift the vehicle out of Park.			
☐ Extended Key fob needs to be within 5 feet of the vehicle to shift out of Park.				
HORN ALARM				
IdleLock will activate the horn if an attempt is made to shift the vehicle out of Park without the key.				
☐ Enabled (Default) ☐ Disabled				
ADDITIONAL FEATURES FOR PURCHASE				
	Auto Lock (-E Option)	☐ Engine Off (-K Op	otion)	
	IdleLock will automatically lock the vehicle doors after the system has been enabled.	Shuts off the engine Brake is pressed wit being detected.		