IdleLock with AutoSense™ Order Spec Sheet (Product Configuration Form)



Directions:

- 1. Complete form to specify custom configurations for your C-IDLE760.
- 2. Submit this form with your order to sales@lgs-group.com.

| Proudly distributed by | |
|--------------------------------------|--|
| LGS GROUP AUTOMOTIVE TECHNOLOGIES | |

| PURCHASER IN | FORMATION | | |
|----------------------|---|------------------------------|---|
| Date | | | |
| Company Name | | INTERNAL ONLY | |
| Contact Name _ | | Config. Name | |
| | | Date Created | |
| | · | Part Number | |
| NOTES | | T art Number | |
| VEHICLE DETAIL | | | |
| VEHICLE DETAIL | | , | |
| Orders will not be p | processed without the install vehicle's make, model | and year. | |
| Vehicle Make | Vehicle Model | | _ |
| Vehicle Year | Vehicle Engine | | _ |
| OUTPUT DELAY | | | |
| OOTFOT DELAT | | | |
| Choose Weapons | s Rack/Rear Hatch Output Delay: | | |
| | (up to 10 mins; Default: 10 secs) | | |
| | , | | |
| KEY FOB | | | |
| Deactivation Ran | de. | | |
| | | iff the webide out of Doule | |
| | Standard Key fob must be in the driver's seat to shi Extended Key fob needs to be within 5 feet of the v | | |
| Ц | Exterided Ney rob needs to be within 3 reet of the v | enicie to shint out of Park. | |
| ADDITIONAL FE | ATURE FOR PURCHASE | | |
| | | | |
| | Auto Lock (-E Option) | | |
| | IdleLock will automatically lock the vehicle doors after the system has been enabled. | | |
| | | | |