Intelligent Switch Module Order Spec Sheet (Product Configuration Form)

Directions:

- 1. Complete form to specify custom configurations for your ISM.
- 2. Submit this form with your order to: sales2@lgs-group.com.

PURCHASER INFORMATION

Date	
Company Name	
Contact Name	
Phone Number	
Email Address	
Vehicle Make	Vehicle Model
Vehicle Year	Vehicle Engine
NOTES	



INTERNAL ONLY	
Config. Name	
Date Created	
Part Number	

Orders will not be processed without the install vehicle's make, model and year. This information is needed for accurate configuration.

STEERING WHEEL BUTTON SETTINGS

Choose version: AUX Buttons (-CA)

AUX MEDIA 3 AUX MUTE AUX 4

Research and a second second

AUX 1 / Seek ▲ Settings:

Choose output:

☐ High True ☐ Low True (Default)

Select one:

- □ Latching □ Momentary (Default)
- "Radio" Timed (30 mins max)

AUX 2 / Seek ▼ Settings:

Choose output: High True Low True (Default) Select one: Latching Momentary (Default) "Radio" Timed _____ (30 mins max)

□ Volume/Seek Buttons (-CV)



AUX 3 / Volume + Settings: Output: Low True (Default)

Select one:

□ Latching □ Momentary (*Default*) □ "Radio" □ Timed _____ (*30 mins max*)

AUX 4 / Volume - Settings:

Output: Low True (Default)

Select one:

□ Latching	□ Momentar	'y <i>(Default)</i>
🗆 "Radio"	Timed	(30 mins max)

NOTES: High True = Power; Low True = Ground. Seek = Left side; Volume = Right side. Latching = toggle on/off; "Radio" = only one active at a time. You must program two or more buttons as "Radio" for feature to function.