

Idle Timer Controller Order Spec Sheet (Product Configuration Form)



Directions:

1. Complete form to specify custom configurations for your ITC.
2. Submit this form with your order to orders@lgs-group.com.

PURCHASER INFORMATION

Date _____
Company Name _____
Contact Name _____
Phone Number _____
Email Address _____
Vehicle Make _____ **Vehicle Model** _____
Vehicle Year _____ Vehicle Engine _____
NOTES _____

INTERNAL ONLY

Config. Name	
Date Created	
Part Number	

Orders will not be processed without the install vehicle's make, model and year. This information is needed for accurate configuration.

SHUTOFF TIMER

Idle Shutoff Timer Duration

For both Parking Brake and non-Parking Brake
_____ Max 3000 Sec (Default PB 300, Non-PB 900 Sec)

COUNTER RESET DISABLE

Disable Engine Shutdown Counter Reset (if applicable)

Removes the ability to reset the shutdown counter using the Service Brake (SB), Park Brake (PB) or Accelerator Pedal (APP)

TEMPERATURE

Engine Temperature for Idle Shutoff

Allows engine to be at a normal operating temperature before system operates

Minimum _____ 0°F to 200°F (Default 100°F)
(For Ford Transit Gas Engines, 170°F is recommended)

OPTIONS

Plug and play ignition harnesses and other options are available; contact sales for further details.