

# Aftermarket Interface Module - AIM605

## Order Spec Sheet (Product Configuration Form)



### Config Options:

- Recommended: Download the AIM Graphical User Interface (GUI) from the [InterMotive website](#), complete the configurations, save and email with your order to: sales@lgs-group.com.
- Or complete this form to specify custom configurations for your AIM. Save and email with your order to: sales@lgs-group.com.

### PURCHASER INFORMATION

Date \_\_\_\_\_

Company Name \_\_\_\_\_

Contact Name \_\_\_\_\_

Phone Number \_\_\_\_\_

Email Address \_\_\_\_\_

**Vehicle Make** \_\_\_\_\_ **Vehicle Model** \_\_\_\_\_

**Vehicle Year** \_\_\_\_\_ Vehicle Engine \_\_\_\_\_

NOTES \_\_\_\_\_

### INTERNAL ONLY

Config. Name	
Date Created	
Part Number	

*Orders will not be processed without the install vehicle's make, model and year. This information is needed for accurate configuration.*

### HIGH IDLE SETTINGS\*

High Idle RPM: *(In increments of 50 RPM)*

RPM Gas \_\_\_\_\_ 900-2200 RPM (Default 1500)

RPM Diesel \_\_\_\_\_ 900-1400 RPM (Default 1200)

*High idle vehicle requirements: TR = Park, SB = Off; RPM at idle*

### SELECT TRIGGER OPTION:

OPTION A  External Input Trigger:  Enabled (Default)  Disabled *High idle engages when ground signal is applied.*

Park Brake Precondition:  Enabled  Disabled (Default) *Must apply Park brake to high idle with input.*

OPTION B  Park Brake Trigger:  Enabled  Disabled (Default) *High idle engages when Park brake is applied.*

### BATTERY SETTINGS

Charge Protect Feature:  Enabled (Default)  Disabled

Low Battery Voltage \_\_\_\_\_ Max 16V (Default 12.5V)

Recovery Voltage \_\_\_\_\_ Max 16V (Default 13.5V)

Recharge Timer \_\_\_\_\_ Max 1800 Secs (Default 300 Secs)

## AIM605 Order Spec Sheet (Product Configuration Form), Page 2

### PROGRAMMABLE DATA OUTPUTS

Choose output settings:

PIN#		CUSTOM OUTPUT LOGIC		DEFAULTS
1*	J6-Pin2	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Engine = Crank, 8 Amps
2	J5-Pin2	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Transmission Range = Park; 0.5 Amps
3	J5-Pin3	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Park Brake = On; 0.5 Amps
4	J5-Pin4	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Transm. Range = Reverse; 0.5 Amps
5	J5-Pin8	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Ignition = On; 0.5 Amps
6†	J5-Pin9	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Engine Running = True; 0.5 Amps
7	J5-Pin10	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Right Turn Signal = On; 0.5 Amps
8‡	J5-Pin11	<input type="checkbox"/> Ground (Default)	<input type="checkbox"/> Power _____	Left Turn Signal = On; 0.5 Amps

\* Requires connecting J6-Pin4 to either 12V or Ground.

† VSS = 2.2Hz/MPH can only be programmed on output #6 as a Ground output (no power option).

‡ CTO can only be programmed on output #8 as a Ground output (no power option).

### DOOR LOCK FUNCTION\*

Lock/Unlock Driver's Door (Default)   
  Lock/unlock All Doors

**\*For J-harness kits (for Global B vehicles):** Locks/unlocks all doors only.